

# PSDF Series Servo Drive



## Product Features

### Specialized For CNC

- Standard Mechatrolink II and Mechatrolink III buses, perfectly adapted to LNC, Syntec, HUST and other CNC systems
- Kalman observer algorithm for faster servo response
- Load perturbation compensation algorithm for smoother processing
- Quadrant bump suppression algorithm for finer processing
- Turret control function

### Smart

- Powerful internal position mode allows for continuous multi-path planning for rich motion control; supports up to 32 data sets for planning, each set of data can be set to the number of pulses or angle required, and internal position mode can be set for speed, acceleration, deceleration and emergency deceleration
- Automatic determination of load inertial mechanical properties, setting optimal gain and shortening system commissioning time

### Stable

- Mechanical resonance frequency analysis, configuration of two sets of trap filters, adjustable frequency (50~5000Hz) and trap depth, effectively overcome low frequency resonance and mechanical end vibration, can set the vibration frequency (1~100Hz) and vibration damping
- Frictional torque compensation reduces the effect of static friction during mechanical commutation and improves command following performance at low speeds

## Specifications

### Model

|                      |                     |                     |                     |                     |
|----------------------|---------------------|---------------------|---------------------|---------------------|
| PSDFAS08□□<br>0.75kW | PSDFAS15□□<br>1.5kW | PSDFAS22□□<br>2.2kW | PSDFAS30□□<br>3kW   | PSDFAS50□□<br>5kW   |
| PSDFBS15□□<br>1.8kW  | PSDFBS25□□<br>3kW   | PSDFBS35□□<br>3.8kW | PSDFBS55□□<br>5.5kW | PSDFBS75□□<br>7.5kW |

### Input Power

#### Control Mode

Three-phase PWM converter sine wave drive

#### Main Power

220V: Single-phase/three phase 220V AC (-15~+10%, 50~60Hz)  
380V: Three-phase 380V AC (-15~+10%, 50~60Hz)

#### Control Power

220V: Single-phase 220V AC (-15~+10%, 50~60Hz)

#### Rated Current

220V: 0.4kW/2.8A, 0.75kW/5.5A, 1.5kW/10A, 2.2kW/12A, 3kW/16A, 5kW/25A  
380V: 1.8kW/5A, 3kW/8A, 3.8kW/12A, 5.5kW/16A, 7.5kW/20A

#### Encoder Feedback

Absolute encoder

### Environment

#### Working Temperature

0~45°C

#### Storage Temperature

-20~65°C

#### Working Humidity

20~85%RH or less (non condensing)

#### Storage Humidity

20~85%RH or less (non condensing)

#### Working And Storage air

Indoor (no direct sunlight), non-corrosive gases, flammable gases, oil mist, dust

#### Altitude

Below 1000m

#### Vibration

5.8m/s<sup>2</sup> (0.6G) below 10~60Hz (Cannot be used continuously at resonant frequency)

#### Insulation And Pressure Resistance

Primary- between F and G, 1 minute under AC1500V

### Control Signals

#### Input

6-channel (DC24V opto-coupler isolation) Input function can be selected according to

#### Output

parameters 4-channel opto-coupler isolated output; output function can be selected according to

#### Communications

parameters MECHATROLINK-II MECHATROLINK-III

#### Control Modes

3 control modes: position control, speed control, torque mode

#### Regenerative Resistance

400W: without; over 750W: with

### Position Control Modes

#### Control Input

Home Recursive Deceleration Switch Signal (/DEC), external latch signal (/EXT 1 to 2), positive rotation prohibited (P-OT), negative rotation prohibited (N-OT), positive rotation side torque limit (/P-CL), negative rotation side torque limit (/N-CL)

#### Control Output

Servo alarm (ALM), position completion (/COIN), velocity consistent detection, brake (/BK), servo motor rotation detection (/TGON), servo ready (/S-RDY), torque limit detection (/CLT), encoder zero output

### Pulse Output

#### Output Pulse Patterns

Phase A, phase B, phase Z: differential output

#### Frequency Dividing Ratio

Arbitrary frequency division

### Communications

#### Communication Protocols

MECHATROLINK- II \ MECHATROLINK- III

#### Transmission Speed

M2: 10 Mbps; M3: 100 Mbps

#### Transmission Period

M2: 250 μsec ~ 8 msec; M3: 31.25 μsec ~ 64 msec

#### Frame Length

M2: 17bytes/32bytes; M3: 32bytes/48bytes

#### Connectable Slave Station NO.

M2: up to 30; M3: up to 62

### Command Methods

#### Command Specifications

Via position control, speed control and torque control of MECHATROLINK

#### Command Input

MECHATROLINK command (such as compliance control, motion, data setting/referencing, monitoring, adjustment and other commands)