

Ø28mm

内置齿轮型

PMG28N 系列

步距角精度: $\pm 8\%$

电阻精度: $\pm 10\%$

电感精度: $\pm 20\%$

环境温度: $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$

绝缘电阻: 最小 $100\text{M}\Omega$ (500VDC条件下)

耐压强度: $650 \pm 50\text{V}$ AC下持续2秒 (有效值)

绝缘等级: E级



小尺寸



低转速



高力矩

技术参数

系列	型号	相数	电压	电阻	牵入转矩	牵入频率	牵出频率	定位转矩	步距角	减速比
			V	Ω	mN.m at 100pps	pps	pps	mN.m	$^{\circ}$	
PMG28N28	PMG28N28-05	2	5	20	≥ 29.4	≥ 600	$\geq 1,000$	≥ 29.4	$5.625^{\circ}/16$	16:1
	PMG28N28-10	2	12	100	≥ 39.4	≥ 600	$\geq 1,000$	≥ 29.4	$5.625^{\circ}/25$	25:1
	PMG28N28-02	2	5	20	≥ 49	≥ 600	$\geq 1,000$	≥ 39.4	$5.625^{\circ}/32$	32:1
PMG28N48	PMG28N48-15	4	12	110	≥ 49	≥ 600	$\geq 1,000$	≥ 39.4	$5.625^{\circ}/36$	36:1
	PMG28N48-06	4	12	60	≥ 49	≥ 600	$\geq 1,000$	≥ 39.4	$5.625^{\circ}/36$	36:1
	PMG28N48-20	4	12	200	≥ 68.8	≥ 600	$\geq 1,000$	≥ 39.4	$5.625^{\circ}/64$	64:1
	PMG28N48-30	4	24	300	≥ 147	≥ 600	$\geq 1,000$	≥ 49	$5.625^{\circ}/64$	64:1
	PMG28N48-02	4	12	200	≥ 98	≥ 600	$\geq 1,000$	≥ 49	$5.625^{\circ}/90$	90:1

外形图

